

OW16061 - Blue - Alcohol Colours



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

OW16061 - Blue - Alcohol Colours

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Additive for varnishes and paints

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Oldwood Colours & Varnishes s.l. Plaza Castilla, 3 28046 Madrid - España Phone: 914118992 customer@oldwood1700.com www.oldwood1700.com

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:





Hazard statements:

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Substances that contribute to the classification

1-methoxy-2-propanol (CAS: 107-98-2)

Additional Labelling:

Do not use in paint spraying equipment

UFI: QWFE-Y10P-H00Q-YT31

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

** Changes with regards to the previous version



OW16061 - Blue - Alcohol Colours



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Non-applicable

3.2 Mixture:

Chemical description: Dye/s in dissolution

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS: 112-34-5		2-(2-butoxyethoxy)e	thanol ⁽¹⁾	ATP CLP00	
EC: Index: REACH:	203-961-6 603-096-00-8 01-2119475104-44- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	¢	50 - <75 %
CAS:	107-98-2	1-methoxy-2-propan	lol ⁽¹⁾	ATP ATP01	
EC: Index: REACH:	203-539-1 603-064-00-3 01-2119457435-35- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	() (*)	5 - <25 %
CAS:	67827-60-5	C.I.Acid blue 260 ⁽¹⁾		Self-classified	
EC: Index: REACH:	267-224-0 Non-applicable 01-2120119696-49- XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412		2,5 - <5 %
CAS: 687-47-8 EC: 211-694-1 Index: 607-129-00-7 REACH: 01-2119516234-49- XXXX		Ethyl (S)-2-hydroxyp	propionate ⁽¹⁾	ATP CLP00	
		Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger		1 - <2,5 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:



SECTION 5: FIREFIGHTING MEASURES (continued)

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene



OW16061 - Blue - Alcohol Colours



SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

- D.- Technical recommendations to prevent environmental risks
- It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m ³	
CAS: 107-98-2 EC: 203-539-1	IOELV (STEL)	150 ppm	568 mg/m ³	
2-(2-butoxyethoxy)ethanol	IOELV (8h)	10 ppm	67,5 mg/m ³	
CAS: 112-34-5 EC: 203-961-6	IOELV (STEL)	15 ppm	101,2 mg/m ³	

DNEL (Workers):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m³	67,5 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Non-applicable


DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	60,7 mg/m ³	40,5 mg/m ³	40,5 mg/m ³
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m ³	Non-applicable

PNEC:

Identification				
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1,1 mg/L
CAS: 112-34-5	Soil	0,32 mg/kg	Marine water	0,11 mg/L
EC: 203-961-6	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg







SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	10 mg/L
CAS: 107-98-2	Soil	4,59 mg/kg	Marine water	1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg
Ethyl (S)-2-hydroxypropionate	STP	Non-applicable	Fresh water	0,32 mg/L
CAS: 687-47-8	Soil	0,145 mg/kg	Marine water	0,032 mg/L
EC: 211-694-1	Intermittent	3,2 mg/L	Sediment (Fresh water)	1,66 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,166 mg/kg

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogran	n	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tr protection	y ract	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks		
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.		
E	- Body protection						

	Pictogram	PPE	Labelling	CEN Standard	Remarks		
		Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.		
		Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007		
F	- Additional emergency measures						

Version: 2 (Replaced 1)

Revised: 21/06/2022



OW16061 - Blue - Alcohol Colours

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



	Emergency measure	Standards	Emergency measure	Standards
	Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
	Environmental exposure of	controls:	-	
	In accordance with the comm	nunity legislation for the protection of and its container. For additional inform		
	With regard to Directive 2010)/75/EU, this product has the followin	g characteristics:	
	V.O.C. (Supply):	22,02 % weight		
	V.O.C. density at 20 °C:	212,59 kg/m³ (212,59 g/	L)	
	Average carbon number:	4,09		
	Average molecular weight	t: 92,65 g/mol		
SECT	TION 9: PHYSICAL AND CH	IEMICAL PROPERTIES **		
9.1	Information on basic phy	sical and chemical properties:		
5.1	For complete information see			
	Appearance:			
	Physical state at 20 °C:	Liquid		
	Appearance:	Transpare	nt	
	Colour:	Blue		
	Odour:	Characteri	stic	
	Odour threshold:	Non-appli		
	Volatility:			
	Boiling point at atmospheric p	pressure: 125 - 231	٥C	
	Vapour pressure at 20 °C:	355 Pa		
	Vapour pressure at 50 °C:	1858,91 P	a (1,86 kPa)	
	Evaporation rate at 20 °C:	Non-appli		
	Product description:			
	Density at 20 °C:	965,3 kg/l	ກ ³	
	Relative density at 20 °C:	0,965		
	Dynamic viscosity at 20 °C:	Non-appli	cable *	
	Kinematic viscosity at 20 °C:	Non-appli	cable *	
	Kinematic viscosity at 40 °C:	Non-appli	cable *	
	Concentration:	Non-appli	cable *	
	pH:	Non-appli	cable *	

Date of compilation: 08/07/2021

Vapour density at 20 °C:

Solubility in water at 20 °C:

Decomposition temperature:

Melting point/freezing point:

** Changes with regards to the previous version

Solubility properties:

ldWood

RNISHES & NATURAL COLOURS

- CONTINUED ON NEXT PAGE -

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable * Non-applicable *

Water-soluble

Partition coefficient n-octanol/water 20 °C:

*Not relevant due to the nature of the product, not providing information property of its hazards.

Version: 2 (Replaced 1)





SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	ES ** (continued)			
	Flammability:				
	Flash Point:	61 °C			
	Flammability (solid, gas):	Non-applicable *			
	Autoignition temperature:	204 °C			
	Lower flammability limit:	Non-applicable *			
	Upper flammability limit:	Non-applicable *			
	Particle characteristics:				
	Median equivalent diameter:	Non-applicable			
9.2	Other information:				
	Information with regard to physical hazard classes:				
	Explosive properties:	Non-applicable *			
	Oxidising properties:	Non-applicable *			
	Corrosive to metals:	Non-applicable *			
	Heat of combustion:	Non-applicable *			
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *			
	Other safety characteristics:				
	Surface tension at 20 °C:	Non-applicable *			
	Refraction index:	Non-applicable *			
	*Not relevant due to the nature of the product, not providing info	ormation property of its hazards.			

** Changes with regards to the previous version

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Increase in temperature	Sunlight	Humidity
Not applicable Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

** Changes with regards to the previous version

OW16061 - Blue - Alcohol Colours



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

VOOC

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:
 - Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

	Identification	Ac	ute toxicity	Genus
** Change	e.withingards to the previous version	LD50 oral	5100 mg/kg	Rat
	CAS: 67827-60-5	LD50 dermal	Non-applicable	
	EC: 267-224-0	LC50 inhalation	Non-applicable	

** Changes with regards to the previous version





SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
C.I.Acid blue 260	LC50	14 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 67827-60-5	EC50	Non-applicable		
EC: 267-224-0	EC50	Non-applicable		

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
2-(2-butoxyethoxy)ethanol	BOD5	0,25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2,08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0,12	% Biodegradable	92 %
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
C.I.Acid blue 260	BOD5	0,02 g O2/g	Concentration	Non-applicable
CAS: 67827-60-5	COD	1,29 g O2/g	Period	Non-applicable
EC: 267-224-0	BOD5/COD	0,01	% Biodegradable	Non-applicable

12.3 Bioaccumulative potential:

Identification	Bioaccur	nulation potential
2-(2-butoxyethoxy)ethanol	BCF	0.46
CAS: 112-34-5	Pow Log	0.56
EC: 203-961-6	Potential	Low
1-methoxy-2-propanol	BCF	3
CAS: 107-98-2	Pow Log	-0.44
EC: 203-539-1	Potential	Low
Mobility in soil:		

** Changes with regards to the previous version

Safety data sheet



OW16061 - Blue - Alcohol Colours



SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Absorption/desorption Volatility 48 7,2E-9 Pa·m³/mol 2-(2-butoxyethoxy)ethanol Koc Henry CAS: 112-34-5 Conclusion Very High Dry soil No EC: 203-961-6 3,395E-2 N/m (25 °C) Surface tension Moist soil No 12.5 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria 12.6 Other adverse effects: Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:





SECTION 14: TRANSPORT INFORMATION (continued)

		continucuj
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4		Non-applicable
14.5	Environmental hazards:	No
-	Special precautions for user	
	Special regulations:	Non-applicable
	Tunnel restriction code:	Non-applicable
	Physico-Chemical properties:	see section 9
	Limited quantities:	Non-applicable
14.7	·	Non-applicable
,	to Annex II of Marpol and	
	the IBC Code:	
Transpo	rt of dangerous goods by sea:	
With rega	rd to IMDG 40-20:	
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5	Marine pollutant:	No
14.6	Special precautions for user	
	Special regulations:	Non-applicable
	EmS Codes:	
	Physico-Chemical properties:	see section 9
	Limited quantities:	Non-applicable
	Segregation group:	Non-applicable
14.7	Transport in bulk according	Non-applicable
	to Annex II of Marpol and	
_	the IBC Code:	
Transpo	rt of dangerous goods by air:	
With rega	rd to IATA/ICAO 2022:	
14.1	UN number:	Non-applicable
14.2	······································	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according	Non-applicable
	to Annex II of Marpol and	
	the IBC Code:	

SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture:
	Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
	Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
	Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
	Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -

Revised: 21/06/2022Version: 2 (Replaced 1)Document generated with Chemeter (www.siam-it.com)





SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 3 % of 2-(2-butoxyethoxy)ethanol by weight. 1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight. 2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010. 3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows: 'Do not use in paint spraying equipment'. Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

New declared substances

2-(2-butoxyethoxy)ethanol (112-34-5)

- 1-methoxy-2-propanol (107-98-2)
- C.I.Acid blue 260 (67827-60-5)

Ethyl (S)-2-hydroxypropionate (687-47-8)

Substances that contribute to the classification (SECTION 2):

- New declared substances
 - 1-methoxy-2-propanol (107-98-2)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements
- Precautionary statements

Information on basic physical and chemical properties (SECTION 9):

· Flash Point

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

** Changes with regards to the previous version







Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. **Classification procedure:** STOT SE 3: Calculation method Eye Irrit. 2: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

dWood

SECTION 16: OTHER INFORMATION ** (continued)

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Document generated with Chemeter (www.siam-it.com)